


LPC-2.MM1

PLC main control module



WWW.SMARTEH.COM



USER MANUAL



LINKEDIN



YOUTUBE



SALES@SMARTEH.SI



+386 5 388 4400

INTRODUCTION


Discover the revolutionary Smarteh LPC-2.MM1 PLC main control module that sets a new standard for performance, scalability, and versatility in building and industrial automation.

The LPC-2.MM1 features a compact, Arm-based System on Module (SoM) package, delivering enhanced computing power and control with a wide array of advanced features. Powered by an ARM architecture processor and a Linux-based OS, the LPC-2.MM1 is future-proof, enabling seamless interface connections and core SoM module upgrades without hardware changes. Effortlessly expand your capabilities by connecting additional input and output modules via an internal bus connector on the right side of the LPC-2.MM1.

Unleash seamless connectivity with Ethernet Daisy chain topology.

Experience the next evolution in networking with Ethernet Daisy Chain Topology—a revolutionary solution designed to simplify and streamline your network infrastructure like never before.

The LPC-2.MM1 is a connectivity powerhouse, featuring two Ethernet Daisy chain ports with fail-safe functionality through an integrated switch for uninterrupted operation during power failures. Additionally, LPC-2.MM1 has a fast Gigabit Ethernet port for independent networking with BMS, third-party PLCs, cloud, or other data acquisition and control systems.



The WiFi antenna is not included in the scope of supply.



WWW.SMARTEH.COM



USER MANUAL



LINKEDIN



YOUTUBE



SALES@SMARTEH.SI



+386 5 388 4400

KEY FEATURES & BENEFITS

➤ Unmatched automation performance in a compact Arm-based SoM


The LPC-2.MM1 PLC-based main control module is powered by an advanced i.MX6 Single (ARM® Cortex™ - A9) @ 1GHz CPU ensuring robust performance for a variety of automation tasks. With its high processing speed and efficiency, this SoM handles complex computations and real-time processing with ease.

➤ Discover Inkscape: A professional and open-source vector GUI editor

Experience the ultimate design freedom with Inkscape, the versatile open-source vector GUI editor that empowers you to create stunning graphical interfaces. Seamlessly integrated with Smarteh IDE, this powerful platform offers limitless possibilities and unmatched flexibility for UI design and PLC functionality. Say goodbye to costly licenses and fees, and embrace a world where your creativity knows no bounds.

➤ Connect remotely to a PLC in the field via a web browser

Access the LPC-2.MM1 PLC from any device through a web browser, utilizing a secure VPN connection or simplified Broadcast transmission.



WWW.SMARTEH.COM



[USER MANUAL](#)



[LINKEDIN](#)






[YOUTUBE](#)



SALES@SMARTEH.SI



[+386 5 388 4400](tel:+38653884400)



KEY FEATURES & BENEFITS

➤ Efficient and scalable connectivity

Ethernet daisy chain enables seamless communication between devices, minimizing latency, ensuring consistent signal strength, and allowing for easy network expansion, thus optimizing overall system performance and scalability. Designed with scalability in mind, the LPC-2.MM1 allows for easy expansion and integration as system requirements grow. Ideal for both small-scale projects and large industrial applications, providing flexibility and future-proofing your investment.

➤ Versatile connectivity

LPC-2.MM1 supports a wide range of connectivity options, including Ethernet connectivity with Modbus TCP/IP Slave (server) and/or Master (client) functionality, BACnet IP (B-ASC), web client with SSL support, Modbus RTU Master or Slave facilitating seamless integration into existing networks.

➤ Compact and robust design

The single compact LPC-2.MM1 main control module minimizes space requirements, making it perfect for applications with limited space. Built to withstand harsh industrial environments, ensuring reliable performance in challenging conditions.



WWW.SMARTEH.COM



USER MANUAL



LINKEDIN



YOUTUBE



SALES@SMARTEH.SI



+386 5 388 4400

KEY APPLICATIONS

➤ Building automation

Ideal for smart building solutions, HVAC systems, lighting control, and energy management. Enhances building efficiency, comfort, and security through intelligent automation.

➤ Industrial automation

Perfect for manufacturing, process control, and industrial IoT applications. Optimizes production processes, reduces downtime, and improves overall productivity.

➤ Smart infrastructure

Suitable for smart city projects, including traffic management, smart grids, and public safety systems. Supports real-time data analysis and decision-making, enhancing urban living standards.



WWW.SMARTEH.COM



USER MANUAL



LINKEDIN



YOUTUBE



SALES@SMARTEH.SI



+386 5 388 4400



GENERAL

1

CPU

i.MX6 Single (ARM® Cortex™-A9)
@ 1GHz

2

RAM

1 GB DDR3

3

NV RAM

512 kB, capacitor backed up
with retention cca. 14 days

4

FLASH

4 GB eMMC 8bits (MLC type)

5

OPERATING SYSTEM

Linux

COMM. PORTS

1

ETHERNET

1x RJ-45, 10/100/1000T IEEE 802.3
2x RJ-45, 10/100T IEEE 802.3

2

WIFI

IEEE 802.11 b/g/n, SMA female connector

3

UART PORT

1x Smarteh bus RJ-12 6/4 non isolated
1x Modbus RTU RS-485 non isolated, 2 wire

4


USB HOST

1x mini B type, device mode or host mode
(USB On-TheGo), high-speed/full-speed

5

RIGHT INTERNAL BUS

For connection to Smarteh I/O and
Communication modules



SPECIFICATIONS

1

POWER CONSUMPTION

Up to 24 W depending on additional modules connected to main module

2

POWER SUPPLY

Rated 24 V DC, 2A
Operational 20 .. 28 V DC

3

TEMPERATURE

Operating 0° ~ 50°C (32° ~ 122°F)
Ambient -20° ~ 60°C (-4° ~ 140°F)

4

MOUNT

DIN EN50022-35 rail mounting

5

ENCLOSURE

Nilit Nilamid B G6 FR C4 30% Glass Fiber Reinforced, Flame Retardant PA6 + MB7035



SMARTTEH d.o.o.

Poljubinj 114, 5220 Tolmin, Slovenia

tel.: + 386(0)5 388 44 00

fax.: + 386(0)5 388 44 01

sales@smarteh.si

www.smarteh.com