

## CYLINDRICAL MORTICE MOUNTED MAGNETIC CONTACTS

### CHARACTERISTICS

HA1

<b>Dimensions with wires L x Ø :</b> MS915 2 and 4 wires = 19 x 9 mm MS915 3 and 5 wires = 22 x 9 mm MS916 = 29 x 19 mm	
<b>Dimensions with screwterminal S L x Ø :</b> MS915 = 29 x 9 mm MS916 = 38 x 19 mm	
<b>Switching Voltage</b>	<b>Switching distance</b>
(NO) 200V DC / 500 mA (CHANGEOVER) 100V DC / 250 mA	MS915 = 12 mm MS916 = 35 mm
<b>MATERIAL :</b>	ABS white
<b>CABLE LENGTH :</b>	<b>2 meters</b> (other cable lengths on request)
<b>OPERATING TEMPERATURE :</b>	from -20° to +70°C
IP 68	



### MAGNETIC CONTACTS MS915

mortice mount - for wood

<b>MS915/AW2</b>	Mortice cylindrical magnetic contact 2 wires 2 m for wood (NO)	0,06 kg
<b>MS915/CW2</b>	Mortice cylindrical magnetic contact 3 wires 2 m for wood (changeover)	0,06 kg
<b>MS915/ALW2</b>	Mortice cylindrical magnetic contact 4 wires 2 m for wood (NO + loop)	0,06 kg
<b>MS915/CLW2</b>	Mortice cylindrical magnetic contact 5 wires 2 m for wood (changeover + loop)	0,1 kg
<b>MS915/AT</b>	2 screws terminal cylindrical magnetic contact 2 m for wood (NO)	0,01 kg
<b>MS915MS</b>	Mounting support for use MS915 range on metal	0,01 kg



### MAGNETIC CONTACTS MS916

mortice mount - for metal

<b>MS916/AW2</b>	Mortice cylindrical magnetic contact 2 wires 2 m for metal door (NO)	0,08 kg
<b>MS916/CW2</b>	Mortice cylindrical magnetic contact 3 wires 2 m for metal door (changeover)	0,08 kg
<b>MS916/ALW2</b>	Mortice cylindrical magnetic contact 4 wires 2 m for metal door (NO + loop)	0,06 kg
<b>MS916/CLW2</b>	Mortice cylindrical magnetic contact 5 wires 2 m for metal door (changeover + loop)	0,08 kg
<b>MS916/AT</b>	2 screws terminal cylindrical magnetic contact 2 m for metal door (NO)	0,03 kg

